

## TECHNICAL SPECIFICATION SHEET FOR CS20-UL

Marketing Information	
Code	CS20-UL
Model	CS20-UL
Capacity [ft <sup>3</sup> ]	20
Capacity [lt]	566
Market/Country	National/Exportation
Dimension with packaging [in]	<b>W:33.5 D:42.19 H:88</b>
Dimension without packaging [in]	<b>W:26 D:32.75 H:83.375</b>
Accessories	
User´s Guide	Yes
Safety Recommendations	Yes
Liquid Evaporating Tray	Yes
Wheels	Yes
Temperature Control	Digital
Technical Characteristics	
Refrigerant	R-404a
Evaporation Temperature [°F]	-18
Condensation Temperature [°F]	109.4
Defrost Method	Electric
Optimal Temperature Range **[°F]	0 or less
Shelves Line	
Quantity (Pieces)	4
Materials	Stainless steel
Clamps	Adjustables
Colors	Gray
Stainless steel positional baskets	2
Doors	
Quantity (Pieces)	1
Door Type	hinged
Door Construction	Solid
Materials	Stainless steel
Color	Stainless steel
Closing method	Seal Self-closing
Glass Quantity in Sandwich	n/a
Handles	
Quantity (Pieces)	1
Materials	Stainless steel
Color	n/a
Finished	
Interior	Stainless steel
Exterior	Stainless steel
Isolation mode	High density polyurethane
Electrical Characteristics	
Nominal Voltage [V]	120
Nominal Current [A]	10.80
Frecuency [Hz]	60
Method of Lighting	Fluorescent lamp
Cooling System	
Compressor (HP)	1/2
Condenser	Self-lubricating coil fan motor
Evaporator	Self-lubricating coil fan motor
Expansion Method	Capillary tube

Specified by NSF\*\* for storage potentially-hazardous foods

Note: All controllers reach temperature from 28 °F to -10 °F

\* W= Weight, D= Depth, H= Height

REVISION: 1  
DATE: 29/05/2013