

## TECHNICAL SPECIFICATION SHEET FOR CS40-UL

|                                    |                                  |
|------------------------------------|----------------------------------|
| <b>Marketing Information</b>       |                                  |
| Code                               | CS40-UL                          |
| Model                              | CS40-UL                          |
| Capacity [ft <sup>3</sup> ]        | 40                               |
| Capacity [lt]                      | 1133                             |
| Market/Country                     | National/Exportation             |
| Dimension with packaging [in]      | <b>W:56.75 D:42.19 H:88</b>      |
| Dimension without packaging [in]   | <b>W:49.875 D:32.75 H:83.375</b> |
| <b>Accessories</b>                 |                                  |
| User´s Guide                       | Yes                              |
| Safety Recommendations             | Yes                              |
| Liquid Evaporating Tray            | Yes                              |
| Wheels                             | Yes                              |
| Temperature Control                | Digital                          |
| <b>Technical Characteristics</b>   |                                  |
| Refrigerant                        | R-404a                           |
| Evaporation Temperature [°F]       | -18                              |
| Condensation Temperature [°F]      | 109.4                            |
| Defrost Method                     | Electric                         |
| Optimal Temperature Range **[°F]   | 0 or less                        |
| <b>Shelves Line</b>                |                                  |
| Quantity (Pieces)                  | 8                                |
| Materials                          | Stainless steel                  |
| Clamps                             | Adjustables                      |
| Colors                             | Gray                             |
| Stainless steel positional baskets | 4                                |
| <b>Doors</b>                       |                                  |
| Quantity (Pieces)                  | 2                                |
| Door Type                          | hinged                           |
| Door Construction                  | Solid                            |
| Materials                          | Stainless steel                  |
| Color                              | Stainless steel                  |
| Closing method                     | Seal Self-closing                |
| Glass Quantity in Sandwich         | n/a                              |
| <b>Handles</b>                     |                                  |
| Quantity (Pieces)                  | 2                                |
| Materials                          | Stainless steel                  |
| Color                              | n/a                              |
| <b>Finished</b>                    |                                  |
| Interior                           | Stainless steel                  |
| Exterior                           | Stainless steel                  |
| Isolation mode                     | High density polyurethane        |
| <b>Electrical Characteristics</b>  |                                  |
| Nominal Voltage [V]                | 120                              |
| Nominal Current [A]                | 11                               |
| Frecuency [Hz]                     | 60                               |
| Method of Lighting                 | Fluorescent lamp                 |
| <b>Cooling System</b>              |                                  |
| Compressor (HP)                    | 3/4                              |
| Condenser                          | Self-lubricating coil fan motor  |
| Evaporator                         | Self-lubricating coil fan motor  |
| Expansion Method                   | Capillary tube                   |

Specified by NSF\*\* for storage potentially-hazardous foods

Note: All controllers reach temperature from 28 °F to -10 °F

\* W= Weight, D= Depth, H= Height

REVISION: 1  
DATE: 29/05/2013