

TECHNICAL SPECIFICATION SHEET FOR PTP21

Marketing Information	
Code	PTP21-ULH
Model	PTP170
Capacity [ft³]	22.45
Capacity [lt]	635.73
Market/Country	National/Exportation
Dimension with packaging [in]*	L:75 D:43.3 H:46.06
Dimension without packaging [in]*	L:67.71 D:35.03 H:40.55
Accessories	
User Guide	Yes
Safety Recommendations	Yes
Liquid Evaporating Tray	Yes
Wheels	Yes
Quantity of ovenproof	9
Material of work table	Sanalite
Temperature Control	Thermostat
Technical Characteristics	
Refrigerant	R134a
Evaporation Temperature [°F]	19.4
Condensation Temperature [°F]	113
Defrost Method	N/A
Optimal Temperature Range ** [°F]	Exhibicion 33.8°F to 41°F
	Storage 33.8°F to 39.2°F
Shelves Line	
Quantity (Pieces)	1
Materials	Steel
Clamps	Adjustable
Colors	White
Doors	
Quantity (Pieces)	1 Door / 2 Drawers
Door Type	Solid
Materials	Stainless steel and plastic
Colors	Stainless steel
Closing method	Manual
Handles	
Quantity (Pieces)	3
Materials	Plastic
Colors	Black
Finished	
Interior	Preprinted white sheet
Exterior	Stainless steel
Isolation mode	High density polyurethane
Electrical Characteristics	
Nominal Voltage [Volts]	127
Nominal Current [A]	7.4
Frecuency [Hz]	60
Method of Lighting	Fluorescent lamp
Cooling System	
Compressor (HP)	(1/3)
Condenser	Forced Ventilation
Evaporator	Forced Ventilation
Expansion Method	Capillary tube

Specified by NSF** Note: All contros reach temperature untill 75F°

* L= Length, D= Depth, H= Height

REVISION: 1
DATE: 17/12/12