

TECHNICAL SPECIFICATION SHEET FOR RS20-UL

Marketing Information	
Code	RS20-UL
Model	RS20-UL
Capacity [ft ³]	20
Capacity [lt]	566
Market/Country	National/Exportation
Dimension with packaging [in]	W:33.5 D:42.19 H:88
Dimension without packaging [in]	W:26 D:32.75 H:83.375
Accessories	
User´s Guide	Yes
Safety Recommendations	Yes
Liquid Evaporating Tray	Yes
Wheels	Yes
Temperature Control	Digital
Technical Characteristics	
Refrigerant	R134a
Evaporation Temperature [°F]	20
Condensation Temperature [°F]	109.4
Defrost Method	n/a
Optimal Temperature Range ** [°F]	32 - 40
Shelves Line	
Quantity (Pieces)	4
Materials	Stainless steel
Clamps	Adjustables
Shelves color	Gray
Stainless steel baskets	2
Doors	
Quantity (Pieces)	1
Door Type	Swing
Door Construction	Solid
Materials	Stainless steel
Color door	Stainless steel
Closing method	Sealable
Glass Quantity in Sandwich	n/a
Handles	
Quantity (Pieces)	1
Materials	Stainless steel
Color	Gray
Finished	
Interior	Stainless steel
Exterior	Stainless steel
Isolation mode	High density polyurethane
Electrical Characteristics	
Nominal Voltage [V]	120
Nominal Current [A]	6
Frecuency [Hz]	60
Method of Lighting	Fluorescent lamp
Cooling System	
Compressor (HP)	1/4
Condenser	Forced Ventilation
Evaporator	Forced Ventilation
Expansion Method	Capillary tube

Specified by NSF** for storage potentially-hazardous foods

Note: All controllers reach temperature from 24 °F to 76 °F

* W= weight, D= Depth, H= Height

REVISION: 1
DATE: 29/05/2013